

Example: Used and Unused CSS



1. example

```
1 <div class="red">Red Text</div>
2 <span id="green">Green Text</span>

1  /* Used */
2  .red {
3    color: #F00;
4  }
5
6  /* Used */
7  #green {
8    color: #0F0;
9  }
10
11 /* Not used */
12 blue{
13   color: #00F;
14 }
15
16 /* Used */
17 div, span {
18   font-weight: bold;
19 }
```

2. example

```
1 <body>
2   <div class="red-spans">
3     <span id="first">Red Text</span>
4     <span>Red Text</span>
5     <span>Red Text</span>
6   </div>
7 </body>
```

```
1  /* Used */
2  body div.red-spans > span {
3    color: #F00;
4  }
5
6  /* Used */
7  #first + span {
8    font-weight: bold;
9  }
10
11 /* Used */
12 #first ~ span {
13   font-weight: bold;
14 }
```

3. example

```
1 <div>
2   <a href="#"></a>
3 </div>
```

```
1  /* Used */
2  a:hover {
3    color: purple;
4  }
5
6  /* Not used */
7  div-p:last-child{
8   color: green;
9  }
10
11 /* Used */
12 a::after {
13   content: "!";
14 }
```

4. example

```
1 <div>
2   <a target="_blank" href="http://example.com"></a>
3 </div>
```

```
1  /* Used */
2  a[target="_blank"] {
3    color: purple;
4  }
5
6  /* Used */
7  a[href^="http:"] {
8    font-weight: bold;
9  }
```

5. example

```
1 <div>
2   <span>Some text</span>
3 </div>
```

```
1 @media screen and (min-width: 500px) {
2   /* Used */
3   span {
4     color: red;
5   }
6 }
7
8 /* Empty media blocks get removed */
9 @media screen and (min-width: 500px) {
10  /* Not used */
11  a {
12    color: blue;
13  }
14 }
```